

15929

Segregation Survey of Certain Lands in SE $\frac{1}{4}$ , Section 9,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

AP 13

T 26 S R 3 W  
S 9  
1972

from which

A fir, 11 ins. diam., bears N. 76° W., 76 lks.  
dist., mkd. AP13 S $\frac{9}{2}$  BT.

A fir, 13 ins. diam., bears N. 33° E., 104 lks.  
dist., mkd. AP13 S9 BT.

Thence

N. 48° 30' E.

1.73

Angle point No. 14, established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with an iron pipe,  $\frac{1}{2}$  in. diam., firmly set, projecting 8 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

AP 14

T 26 S R 3 W  
S 9  
1972

from which

A fir, 15 ins. diam., bears N. 45° E., 46 lks.  
dist., mkd. AP14 S9 BT.

A fir, 11 ins. diam., bears N. 50° W., 34 lks.  
dist., mkd. AP14 S9 BT.

.Deposit iron pipe alongside iron post.

Thence

S. 86° 50' E.

1.52

Angle point No. 15, established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with an iron pipe,  $\frac{1}{2}$  in. diam., firmly set, projecting 8 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

AP 15

T 26 S R 3 W  
S 9  
1972

from which

A fir, 15 ins. diam., bears N. 62° E., 17 lks.  
dist., mkd. AP15 S BT.