



Segregation Survey of Certain Lands in SE $\frac{1}{4}$ , Section 9,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 15 ins. diam., bears N. 76° W., 52 lks. dist., mkd. AP15 S9 BT.</p> <p>Deposit iron pipe alongside iron post.</p> <p>Thence</p> <p>S. 72° 57' E.</p>
4.69	<p>Angle point No. 16, established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with a wooden post, 3 x 3 x 20 ins., firmly set, projecting 10 ins. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>AP 16</p> <p>T 26 S R 3 W S 9 1972</p> </div> <p>from which</p> <p>A fir, 12 ins. diam., bears N. 18° E., 48 lks. dist., mkd. AP16 S9 BT.</p> <p>A fir, 14 ins. diam., bears S. 76° W., 41 lks. dist., mkd. AP16 S9 BT.</p> <p>Deposit wooden post alongside iron post.</p> <p>Thence</p> <p>S. 72° 38' E.</p>
3.24	<p>Angle point No. 17, established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with a wooden post, 3 x 3 x 24 ins., firmly set, projecting 13 ins. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>AP 17</p> <p>T 26 S.R 3 W S 9 1972</p> </div> <p>from which</p> <p>A fir, 13 ins. diam., bears N. 15° E., 29 lks. dist., mkd. AP17 S9 BT.</p> <p>A cedar, 13 ins. diam., bears N. 55° W., 57 lks. dist., mkd. AP17 S9 BT.</p> <p>Deposit wooden post alongside iron post.</p> <p>Thence</p>