

15931

Segregation Survey of Certain Lands in SE $\frac{1}{4}$, Section 9,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

S. 47° 47' E.

1.85

Point for angle point No. 18, 100 ft. normal dist. from the left bank of the North Umpqua River.

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

117280.

AP 18
T 26 S R 3 W
S 9
1972

from which

A fir, 15 ins. diam., bears N. 20° E., 53 lks. dist., mkd. AP18 S9 BT.

A fir, 20 ins. diam., bears N. 11° W., 96 lks. dist., mkd. AP18 S9 BT.

Thence

S. 70° 15' E., parallel to and 100 ft. dist. from the left bank of the North Umpqua River.

3.46

Angle point No. 19, on the line bet. secs. 9 and 10, 100 ft. normal dist. from the left bank of the North Umpqua River, hereinbefore described.

The following traverse of the mean high water line on the right bank of the North Umpqua River is provided for informational purposes only.

From the witness point on the E. and W. center line of sec. 9, on the right bank of the North Umpqua River, hereinbefore described.

Along the top of a well defined bank, 6 to 10 ft. high, through scattered timber and light undergrowth.

S. 38° 15' W., 8.90 chs.

S. 21° 15' W., 10.30 chs.

S. 35° 45' W., 5.20 chs.

S. 46° 11' W., 4.12 chs.

To special meander cor. on the N. and S. center line of sec. 9, hereinbefore described.

The following traverse of the mean high water line on the left bank of the North Umpqua River is provided for informational purposes only.

From the special meander cor. at the intersection of the left bank of the North Umpqua River with the N. and S. center line of sec. 9, established by Mensch, in 1924, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.