

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>Beginning at the cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by Milo Godfrey, Deputy County Surveyor, in 1961, occupied by the original corner tree, a grand fir, 28 ins. diam., with healed blazes on NE., SE., SW., and NW. faces, from which the remains of the original bearing trees:</p> <p>A fir, 33 ins. diam., bears N. 5° E., 25 lks. dist., with healed blaze.</p> <p>A fir, 48 ins. diam., bears S. 33½° E., 72 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>A fir, 40 ins. diam., bears N. 37½° W., 47 lks. dist., no marks visible on open blaze.</p> <p>and bearing trees and a reference monument mkd. by Godfrey</p> <p>A fir, 10 ins. diam., bears N. 50° E., 74 lks. dist., with healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 21½° E., 31 lks. dist., with healed blaze.</p> <p>A hemlock, 10 ins. diam., bears S. 16° W., 69 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>A chinquapin, 13 ins. diam., bears N. 10½° W., 39 lks. dist., with fragmentary scribe marks visible on partially open blaze.</p> <p>An iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, bears West, 0.04 chs. dist., with brass cap mkd. COUNTY SURVEYORS OFFICE T22S R6W S16 S17 S20 S21 1961.</p> <p>N. 0° 40' W., bet. secs. 16 and 17, marking and blazing the true line.</p> <p>Ascend 30 ft. over SE. slope, through scattered timber and dense undergrowth.</p>
1.40	Spur, slopes S. 70° E.; desc. 195 ft. over NE. slope.
13.50	Bottom of descent, slopes E.; asc. 15 ft. over SE. slope.
15.65	Gravelled road, 30 lks. wide, bears N. 20° W. and S. 5° E.
15.80	Spur, slopes E.; desc. 55 ft. over NE. slope.
30.90	Spur, slopes N. 45° W.; desc. 65 ft. over NW. slope.
32.20	Creek, 3 lks. wide, course N. 30° E.; asc. 35 ft. over NE. slope.
40.16	<p>Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>