

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

$\frac{1}{4}$
S 17|S 16
T 22 S R 6 W
1976

from which

A fir, 8 ins. diam., bears N. $73\frac{1}{2}^{\circ}$ E., 94 lks.
dist., mkd. $\frac{1}{4}$ S16 BT.

A grand fir, 5 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ W., 66
lks. dist., mkd. $\frac{1}{4}$ S17 BT.

Ascend 50 ft. over SE. slope.

45.35 Ridge, bears N. 75° E. and S. 75° W.; desc. 375 ft. over
broken N. slope.

60.24 Point for the N 1/16 sec. cor. of secs. 16 and 17.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

N 1/16
S 17|S 16
1976

from which.

A fir, 12 ins. diam., bears S. $70\frac{1}{2}^{\circ}$ E., 18 lks.
dist., mkd. N 1/16 S16 BT.

A fir, 14 ins. diam., bears N. $60\frac{1}{2}^{\circ}$ W., 15 lks.
dist., mkd. N 1/16 S17 BT.

Descend 65 ft. over NW. slope.

75.55 Dry creek bed, 10 lks. wide, course E.; asc. 5 ft. over
S. slope.

77.55 Top of ascent, slopes W.; desc. 20 ft. over N. slope.

78.50 Elk Creek, 100 lks. wide, course S. 70° W.; asc. 40 ft.
over SW. slope.

80.32 The cor. of secs. 8, 9, 16, and 17, perpetuated and re-
corded by Milo Godfrey, Deputy County Surveyor, in 1961,
monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set,
projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 22 S R 6 W
S 8|S 9
S 17|S 16
1961

from which the remains of the original bearing trees

A fir snag, 40 ins. diam., bears S. 36° W., 43
lks. dist., no marks visible on decayed bark
blaze.

and bearing trees mkd. by Godfrey

A white oak, 14 ins. diam., bears N. $11\frac{1}{2}^{\circ}$ E., 11
lks. dist., with healed blaze.