

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>An ash, 18 ins. diam., bears S. 72½° E., 42 lks. dist., with healed blaze.</p> <p>A white oak, 10 ins. diam., bears S. 66½° W., 48 lks. dist., with healed blaze.</p> <p>A maple, 12 ins. diam., bears N. 49½° W., 48½ lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, madrone, alder, myrtle, and chinquapin; undergrowth, salal, poison oak, Oregon grape, vine maple, hazel, rhododendron, and fern.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21. S. 89° 31' W., bet. secs. 17 and 20.</p> <p>Ascend 30 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
1.85	Top of ascent, slopes S.; desc. 55 ft. over SW. slope.
7.95	Ravine, drains S. 20° E.; asc. 335 ft. over SE. slope.
15.15	Ridge, bears N. 25° E. and S. 35° W.; desc. 185 ft. over NW. slope.
19.40	Ravine, drains N. 15° W.; asc. 40 ft. over NE. slope.
21.80	Top of ascent, slopes N.; desc. 80 ft. over NW. slope.
25.70	Ravine, drains N. 30° E.; asc. 175 ft. over NE. slope.
29.45	Spur, slopes N. 20° W.; desc. 225 ft. over NW. slope.
39.94	Point for the ¼ sec. cor. of secs. 17 and 20, determined by the method of broken boundaries; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> ¼ S 17 S 20 T 22 S R 6 W 1976 </p> <p>from which:</p> <p>A fir, 4 ins. diam., bears N. 35½° W., 23½ lks. dist., mkd. ¼ S17 BT.</p> <p>A fir, 7 ins. diam., bears S. 54° E., 13 lks. dist., mkd. ¼ S20 BT.</p>
	<p>S. 89° 29' W., beginning new measurement.</p> <p>Descend 370 ft. over NW. slope.</p>
9.70	Lancaster Creek, 4 lks. wide, course N. 20° E.; asc. 75 ft. over NE. slope.
12.90	Top of ascent, slopes N.; desc. 5 ft. over NW. slope.