

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
1.05	Creek, 5 lks. wide, course N. 10° E.; desc. 10 ft. over NE. slope.
3.10	Bottom of descent, slopes E.; asc. 20 ft. over SE. slope.
6.25	Spur, slopes E.; desc. 140 ft. over NE. slope.
17.95	Creek, 5 lks. wide, course N. 25° W.; asc. 35 ft. over SW. slope.
20.75	Spur, slopes W.; desc. 80 ft. over NW. slope.
23.70	Creek, 8 lks. wide, course N. 40° E.; asc. 175 ft. over SE. slope.
24.35	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
36.20	Spur, slopes E.; desc. 190 ft. over N. slope.
40.70	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$   
 S 18 | S 17  
 T 22 S R 6 W  
 1976

F D O K  
 M 121-43  
 Dec. 94

from which

A fir, 6 ins. diam., bears N. 43° E., 61 lks. dist., mkd. ¼ S17 BT.

A cedar, 16 ins. diam., bears S. 20¼° W., 67 lks. dist., mkd. ¼ S18 BT.

Corner falls on right bank of creek, 3 lks. wide, bears S. 85° E. and N. 85° W., course S. 85° E.

Ascend 415 ft. over S. slope.

53.00	Spur, slopes S. 50° E.; desc. 40 ft. over NE. slope.
54.30	Head of ravine, drains E.; asc. 50 ft. over SE. slope.
56.95	Spur, slopes N. 45° E.; desc. 260 ft. over NE. slope.
63.30	Wet ravine, drains N. 75° E.; asc. 20 ft. over SE. slope.
64.50	Spur, slopes N. 45° E.; desc. 320 ft. over NE. slope.
81.40	The cor. of secs. 7, 8, 17, and 18, perpetuated and recorded by Francis L. Ingram, County Surveyor, in 1976, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 22 S R 6 W  
 S 7 | S 8  
 S 18 | S 17  
 1976

F D O K  
 M 121-43  
 Dec. 94

from which the remains of the original bearing trees