

15946

Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim No. 37, T. 22 S., R. 6 W.,
Willamette Meridian, Oregon

CHAINS	
80.29	S. 59° 54' E., along the N. bdy. of Claim No. 37. The NE. cor. of Donation Land Claim No. 37.
	Subdivision of Section 17, T. 22 S., R. 6 W., Willamette Meridian, Oregon
	From the $\frac{1}{4}$ sec. cor. of secs. 17 and 20. N. 0° 56' W., on the N. and S. center line of sec. 17, marking and blazing the true line. Descend 150 ft. over NW. slope, through heavy timber and dense undergrowth.
3.85	Ravine, drains N. 60° W.; asc. 15 ft. over SW. slope.
6.00	Top of ascent, slopes W.; desc. 280 ft. over NW. slope.
16.05	Creek, 3 lks. wide, course W.; asc. 10 ft. over SW. slope.
17.10	Spur, slopes N. 80° W.; desc. 15 ft. over NW. slope.
18.00	Creek, 1 lk. wide, course S. 85° W.; asc. 35 ft. over SW. slope.
24.50	Spur, slopes N. 70° W.; desc. 10 ft. over NW. slope.
25.25	Ravine, drains N. 55° W.; asc. 15 ft. over SW. slope.
29.10	Gravelled road, 30 lks. wide, bears N. 30° E. and S. 30° W.
31.10	Spur, slopes W.; desc. 20 ft. over NW. slope.
33.40	Ravine, drains N. 70° W.; asc. 20 ft. over SW. slope.
38.60	Spur, slopes S. 80° W.; desc. 2 ft. over NW. slope.
40.43	Point for the center $\frac{1}{4}$ sec. cor. of sec. 17, at inter- section with the E. and W. center line. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C $\frac{1}{4}$ S 17 T 22 S R 6 W 1976 from which A fir, 22 ins. diam., bears N. 30° E., 39 lks. dist., mkd. C $\frac{1}{4}$ S17 BT. A grand fir, 8 ins. diam., bears S. 38 $\frac{1}{2}$ ° W., 27 $\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S17 BT. Descend 70 ft. over NW. slope.
45.85	Ravine, drains W.; asc. 65 ft. over SW. slope.
50.60	Spur, slopes N. 60° W.; desc. 145 ft. over NW. slope.
60.635	Point for the center N 1/16 sec. cor. of sec. 17.