

15948

Subdivision of Section 17, T. 22 S., R. 6 W.,
Willamette Meridian, Oregon

CHAINS																
14.15	Ravine, drains N. 40° E.; asc. 120 ft. over NE. slope.															
18.05	Dirt road, 50 lks. wide, bears N. 5° E. and S. 5° W.															
21.10	Gravelled road, 30 lks. wide, bears N. 45° W. and S. 45° E.															
22.25	Spur, slopes N.; desc. 255 ft. over NW. slope.															
24.30	Gravelled road, 30 lks. wide, bears N. 30° E. and S. 30° W.															
40.15	The center $\frac{1}{4}$ sec. cor. of sec. 17. Descend 185 ft. over NW. slope.															
52.80	Lancaster Creek, 5 lks. wide, course N. 15° W.; asc. 85 ft. over NE. slope.															
55.55	Dirt road, 20 lks. wide, bears N. 5° E. and S. 5° W.															
56.85	Spur, slopes N. 30° W.; desc. 90 ft. over NW. slope.															
68.75	Creek, 8 lks. wide, course N. 30° E.; asc. 85 ft. over SE. slope.															
70.65	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.															
73.95	Top of ascent, slopes S.; desc. 15 ft. over SW. slope.															
80.00	Creek, 3 lks. wide, course S. 85° E.; asc. slightly along creek bottom.															
80.31	The $\frac{1}{4}$ sec. cor. of secs. 17 and 18.															
	From the N $\frac{1}{16}$ sec. cor. of secs. 16 and 17. N. 89° 55' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 17. Descend 80 ft. over NW. slope, through heavy timber and dense undergrowth.															
8.65	Elk Creek, 100 lks. wide, course S. 20° W.; asc. 25 ft. over SE. slope.															
17.85	Top of ascent, slopes S.; desc. 5 ft. over SW. slope.															
18.15	Enter open field, edge bears N. 10° E. and S. 10° W.															
22.175	Intersect the E. bdy. of Donation Land Claim No. 37. Point for the crossing closing cor. of the E. and W. center line of the NE $\frac{1}{4}$ of sec. 17 with the E. bdy. of Claim No. 37. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.															
	<table style="margin: auto;"> <tr> <td>D L C</td> <td></td> <td></td> </tr> <tr> <td>37</td> <td style="border-left: 1px solid black; border-right: 1px solid black;"></td> <td></td> </tr> <tr> <td>N</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S</td> <td>N CCC</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">17</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">1976</td> <td></td> </tr> </table>	D L C			37			N	S	N CCC		17			1976	
D L C																
37																
N	S	N CCC														
	17															
	1976															
	from which A fir, 6 ins. diam., bears N. 88 $\frac{1}{2}$ ° E., 290 $\frac{1}{2}$ lks. dist., mkd. T22S R6W S17 CCC BT. A fir, 8 ins. diam., bears S. 60 $\frac{1}{2}$ ° E., 226 lks. dist., mkd. T22S R6W S17 CCC BT. Set a 7 ft. steel fence post alongside iron post. From this point, the SE. cor. of Claim No. 37, bears S. 30° 02' W., 8.845 chs. dist., hereinbefore described. Descend 15 ft. over SW. slope.															
26.00	Enter timber, edge bears N. 30° W. and S. 45° E.															