

Remonumentation of Certain Original Corner Points,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 28 ins. diam., bears S. 73° W., 216 lks. dist., with scribe marks BT visible on bark blaze. (Record, 244 lks., and distance on slope.)

A fir, 30 ins. diam., bears N. 35½° W., 86½ lks. dist., with scribe marks T 2 R BT visible on bark blaze. (Record, N. 28° W., 105 lks., and distance on slope.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 8 W
S 3 | S 2
S 10 | S 11
1977

from which new bearing trees

A fir, 12 ins. diam., bears N. 8° E., 23½ lks. dist., mkd. T26S R8W S2 BT.

A fir, 18 ins. diam., bears S. 28° E., 6 lks. dist., mkd. T26S R8W S11 BT.

A fir, 13 ins. diam., bears N. 88° W., 29 lks. dist., mkd. T26S R8W S3 BT.

The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by Robert C. Adamek, Registered Land Surveyor No. 999, in 1974, for Weyerhaeuser Timber Company, monumented with an iron bolt, ¾ in. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees:

A sawed fir stump, 34 ins. diam., bears N. 32° E., 26 lks. dist., no marks visible.

A sawed fir stump, 50 ins. diam., bears N. 83° W., 51 lks. dist., with scribe marks T26S R visible on bark blaze.

and the remains of bearing trees mkd. by Adamek

A sawed cedar stump, 33 ins. diam., bears S. 53° E., 70 lks. dist., with a nail with "W" embossed on head, at base.

A sawed cedar stump, 28 ins. diam., bears S. 47½° W., 55 lks. dist., with a nail with "W" embossed on head, at base.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. dia., 24 ins. in the ground, directly over iron bolt, with brass cap mkd.

T 26 S R 8 W
S 9 | S 10
S 16 | S 15
1977

No suitable trees available within limits.