

15954

Remonumentation of Certain Original Corner Points,  
T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Set a 5 ft. steel fence post alongside iron post.

Corner is located in open, logged area.

The  $\frac{1}{4}$  sec. cor. of secs. 9 and 10, determined at record bearing and distance from the remains of the original bearing trees:

An oak snag, 6 ins. diam., bears N.  $66^\circ$  E., 11 lks. dist., no marks visible on decayed blaze.

A fir, 30 ins. diam., bears N.  $36^\circ$  W., 4 lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible on bark blaze, and a nail with "W" embossed on head, at base.

and a bearing tree of which I have no record

A fir, 25 ins. diam., bears N.  $72\frac{1}{2}^\circ$  E.,  $35\frac{1}{2}$  lks. dist., with a nail with "W" embossed on head, at base.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 8 W

$\frac{1}{4}$   
S 9 | S 10  
1977

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, determined at record bearing and distance from the remaining original bearing tree:

A fir, 52 ins. diam., bears N.  $20^\circ$  W., 104 lks. dist., with fragmentary scribe marks visible on weathered bark blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 8 W

$\frac{1}{4}$   $\frac{S 3}{S 10}$   
1977

from which new bearing trees

A fir, 20 ins. diam., bears N.  $66\frac{1}{2}^\circ$  E., 32 lks. dist., mkd.  $\frac{1}{4}$  S3 BT.

A fir, 21 ins. diam., bears S.  $75^\circ$  E., 2 lks. dist., mkd.  $\frac{1}{4}$  S10 BT.