

15957

## T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The following field notes describes the remonumentation of certain original corner points, township 26 south range 9 west, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the Coos Bay District Manager for administrative purposes of the Bureau of Land Management.

The mean magnetic declination is 20° E.

Subdivisions, T. 26 S., R. 9 W.,  
Willamette Meridian, Oregon

(Remonumenting corners established by John W. Meldrum,  
U. S. Deputy Surveyor, in 1896-97)

The cor. of secs. 11, 12, 13, and 14, determined at record bearing and distance from the remains of the original bearing trees:

A fir stump, 50 ins. diam., bears N. 85½° E., 94 lks. dist., with illegible scribe marks visible on bark.

A fir, 40 ins. diam., bears N. 19½° W., 32 lks. dist., with scribe marks T26S R9W S11 BT visible on bark.

and bearing trees of which I have no record

A fir, 10 ins. diam., bears N. 51½° E., 46 lks. dist., with scribe marks T26S R9W S12 BT visible on open blaze.

A madrone, 8 ins. diam., bears S. 44° E., 32 lks. dist., with scribe marks T26S R9W S13 BT visible on open blaze.

A fir, 14 ins. diam., bears S. 59° W., 53 lks. dist., with scribe marks T26S R9W S14 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W  
S 11 | S 12  
S 14 | S 13  
1973

The cor. of secs. 14, 15, 22, and 23, determined at record distance from the remaining original bearing trees:

A fir, 22 ins. diam., bears N. 10½° E., 42 lks. dist., with illegible scribe marks visible on opened blaze. (Record, N. 40° E.)