

Remonumentation of Certain Original Corner Points,
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 36 ins. diam., bears S. 68° E., 39 lks. dist., with illegible scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W
S 15 | S 14
S 22 | S 23
1973

from which new bearing trees

A fir, 20 ins. diam., bears S. 29° W., 70½ lks. dist., mkd. T26S R9W S22 BT.

A fir, 22 ins. diam., bears N. 21° W., 67 lks. dist., mkd. T26S R9W S15 BT.

The ¼ sec. cor. of secs. 14 and 23, determined at record bearing and distance from the original bearing trees:

A fir, 40 ins. diam., bears N. 48½° E., 49 lks. dist., with healed blaze.

A fir, 50 ins. diam., bears S. 48½° W., 24 lks. dist., with scribe marks ¼ S BT visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W
¼ S 14
S 23
1973

The ¼ sec. cor. of secs. 14 and 15, determined at record bearing and distance from the remains of the original bearing trees:

A decayed alder root crown, size indeterminate, bears S. 23° E., 127 lks. dist., no marks visible.

A fir, 40 ins. diam., bears N. 65½° W., 3 lks. dist., with scribe mark T visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 9 W
¼
S 15 | S 14
1973

from which a new bearing tree