

15959

Remonumentation of Certain Original Corner Points,
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A white fir, 36 ins. diam., bears S. 18° E., 142
lks. dist., mkd. $\frac{1}{4}$ S14 BT.

The cor. of secs. 10, 11, 14, and 15, determined at record
bearing and distance from the remaining original bearing
trees:

A myrtle, 14 ins. diam., bears N. 65 $\frac{1}{2}$ ° E., 65 lks.
dist., with illegible scribe marks visible on
opened blaze.

A cedar, 24 ins. diam., bears S. 30° W., 25 lks.
dist., with healed blaze.

and a bearing tree of which I have no record

A myrtle, 50 ins. diam., bears S. 3° W., 27 lks.
dist., with scribe marks NE S15 BT visible on
open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins.
in the ground, to solid rock, and in a mound of stone,
4 ft. base, to top, with brass cap mkd.

T 26 S R 9 W	
S 10	S 11
S 15	S 14
1973	

No other suitable trees available within limits.

The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, determined at record
distance from the remains of the original bearing trees:

A fir snag, 54 ins. diam., bears N. 34° E., 39
lks. dist., with illegible scribe marks visible
on opened blaze.

A fir stump, 48 ins. diam., bears N. 37° W., 69
lks. dist., no marks visible. (Record, N. 33° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 26 S R 9 W	
$\frac{1}{4}$	
S 33	S 34
1973	

from which new bearing trees

A fir, 7 ins. diam., bears S. 24° E., 85 lks.
dist., mkd. $\frac{1}{4}$ S34 BT.

A fir, 10 ins. diam., bears S. 39° W., 87 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S33 BT.

The cor. of secs. 21, 22, 27, and 28, determined at
record bearing and distance from the remains of the
original bearing trees: