

15960

Remonumentation of Certain Original Corner Points,  
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A yew snag, 16 ins. diam., bears N. 32° E., 58 lks. dist., with illegible scribe marks visible on open and decayed blaze.

A yew snag, 18 ins. diam., bears S. 34½° E., 100 lks. dist., no marks visible on open and decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W	
S 21	S 22
S 28	S 27
1973	

from which new bearing trees

A cedar, 38 ins. diam., bears N. 31° E., 116 lks. dist., mkd. T26S R9W S22 BT.

A hemlock, 10 ins. diam., bears S. 37° E., 44½ lks. dist., mkd. T26S R9W S27 BT.

A hemlock, 18 ins. diam., bears S. 10° W., 71 lks. dist., mkd. T26S R9W S28 BT.

A cedar, 48 ins. diam., bears N. 9° W., 36 lks. dist., mkd. T26S R9W S21 BT.

The ¼ sec. cor. of secs. 21 and 22, determined at record bearing and distance from the remains of the original bearing trees:

A hemlock stump, 16 ins. diam., bears N. 72° E., 34 lks. dist., no marks visible.

A maple, 16 ins. diam., bears N. 21° W., 29 lks. dist., with scribe mark B visible on opened blaze.

and bearing trees of which I have no record

A hemlock, 10 ins. diam., bears N. 64° E., 42 lks. dist., with scribe marks ¼ S22 BT visible on open blaze.

A cedar, 12 ins. diam., bears S. 45° W., 33 lks. dist., with scribe marks ¼ S21 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W	
¼	
S 21	S 22
1973	

The cor. of secs. 15, 16, 21, and 22, determined at record bearing and distance from the remaining original bearing trees: