

15961

Remonumentation of Certain Original Corner Points,
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 36 ins. diam., bears S. 77° E., 29 lks.
dist., with healed blaze.

A fir, 36 ins. diam., bears N. 43½° W., 30 lks.
dist., with healed blaze.

and bearing trees of which I have no record

A fir, 72 ins. diam., bears N. 26° E., 29 lks.
dist., with scribe marks T26S R9W S15 BT
visible on bark blaze.

A maple, 16 ins. diam., bears S. 23½° W., 38½
lks. dist., with scribe marks S21 BT visible
on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

| |
|--------------|
| T 26 S R 9 W |
| S 16 S 15 |
| S 21 S 22 |
| 1973 |

The cor. of secs. 9, 10, 15, and 16, determined at record
bearing and distance from the remains of the original
bearing trees:

A root hole, bears S. 15½° E., 226 lks. dist., with
a down fir alongside, 30 ins. diam., with scribe
marks BT visible on opened blaze.

An alder, 18 ins. diam., bears N. 29° W., 82 lks.
dist., with illegible scribe marks visible on
opened and decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

| |
|--------------|
| T 26 S R 9 W |
| S 9 S 10 |
| S 16 S 15 |
| 1973 |

from which new bearing trees

A maple, 9 ins. diam., bears N. 13° E., 38 lks.
dist., mkd. T26S R9W S10 BT.

A hemlock, 10 ins. diam., bears S. 47° E., 31 lks.
dist., mkd. T26S R9W S15 BT.

A fir, 14 ins. diam., bears S. 40° W., 57 lks.
dist., mkd. T26S R9W S16 BT.

A fir, 14 ins. diam., bears N. 28° W., 45 lks.
dist., mkd. T26S R9W S9 BT.

From this point, a locally established corner of which I
have no record, bears S. 42° W., 0.12 chs. dist., monu-
mented with an aluminum pipe, 2½ ins. diam., firmly set,
projecting 8 ins. above ground, from which locally mkd.
bearing trees: