

Remonumentation of Certain Original Corner Points,
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 28 ins. diam., bears N. 9° E., 64 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 7° E., 52 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 76° W., 17 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 41° W., 13 lks. dist., with scribe marks SE S9 BT visible on opened blaze.

The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, determined at record bearing and distance from the remains of the original bearing trees:

A fir snag, 26 ins. diam., bears N. 43° W., 19 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on bark.

A root hole, bears S. 46° E., 8 lks. dist., with a down fir alongside, 28 ins. diam., with scribe marks BT visible on opened blaze.

and bearing trees of which I have no record

A hemlock, 10 ins. diam., bears N. 83° W., 12 lks. dist., with scribe marks $\frac{1}{4}$ S28 BT visible on open blaze.

A hemlock, 14 ins. diam., bears S. 36° E., 25 lks. dist., with scribe marks $\frac{1}{4}$ S33 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W

$\frac{1}{4}$ $\frac{S 28}{S 33}$

1973

The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, determined at record bearing and distance from the remains of the original bearing trees:

A maple snag, 34 ins. diam., bears N. 57° E., 56 lks. dist., no marks visible on decayed blaze.

A root hole, bears N. 17° W., 24 lks. dist., with a down cedar alongside, 30 ins. diam., with illegible scribe marks visible on open and decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.

T 26 S R 9 W

$\frac{1}{4}$ S 29 | S 28

1973