

15963

Remonumentation of Certain Original Corner Points,  
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A cedar stump, 30 ins. diam., bears N. 70° E., 128 lks. dist., mkd.  $\frac{1}{4}$  S28 BT.

A cedar, 36 ins. diam., bears S. 30° W., 110 lks. dist., mkd.  $\frac{1}{4}$  S29 BT.

The cor. of secs. 20, 21, 28, and 29, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 37 $\frac{1}{2}$ ° E., 44 lks. dist., with a down and decayed hemlock alongside, size indeterminate, no marks visible on decayed blaze.

A fir, 48 ins. diam., bears S. 28° E., 46 lks. dist., with illegible scribe marks visible on bark.

A hemlock stump, 20 ins. diam., bears S. 67 $\frac{1}{2}$ ° W., 18 lks. dist., no marks visible on opened and decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 9 W	
S 20	S 21
S 29	S 28
1973	

from which new bearing trees

A hemlock, 12 ins. diam., bears N. 61° E., 42 $\frac{1}{2}$  lks. dist., mkd. T26S R9W S21 BT.

A hemlock, 14 ins. diam., bears S. 48° W., 20 lks. dist., mkd. T26S R9W S29 BT.

A hemlock, 8 ins. diam., bears N. 43° W., 20 lks. dist., mkd. T26S R9W S20 BT.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, determined at record bearing and distance from the remains of the original bearing trees:

A hemlock snag, 14 ins. diam., bears S. 40° E., 18 lks. dist., with illegible scribe marks visible on open and decayed blaze.

A root hole, bears N. 40° W., 20 lks. dist., with a down hemlock alongside, 26 ins. diam., no marks visible.

and the remains of bearing trees of which I have no record

A hemlock, 18 ins. diam., bears N. 49 $\frac{1}{2}$ ° E., 54 lks. dist., with scribe marks  $\frac{1}{4}$  S21 BT visible on partially healed blaze.

A hemlock snag, 16 ins. diam., bears S. 49° W., 21 lks. dist., with scribe marks  $\frac{1}{4}$  S20 BT visible on open blaze.