

Remonumentation of Certain Original Corner Points,  
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W

S 20 | S 21  
1973

No suitable tree available within limits in sec. 20.

The cor. of secs. 16, 17, 20, and 21, monumented with the original basalt stone, 18 x 12 x 5 ins., firmly set 10 ins. in the ground, mkd. with 4 notches on E. and 3 notches on S. edges, from which the remains of the original bearing trees:

A fir stump, 60 ins. diam., bears N.  $25^{\circ}$  E., 35 lks. dist., with scribe marks BT visible on bark.

A cedar stump, 18 ins. diam., bears N.  $57^{\circ}$  W., 34 lks. dist., no marks visible.

and the remains of bearing trees of which I have no record

A fir, 20 ins. diam., bears S.  $31\frac{1}{2}^{\circ}$  E., 125 lks. dist., with scribe marks T26S R9W S21 BT visible on open blaze.

A fir stump, 36 ins. diam., bears S.  $67^{\circ}$  W., 58 lks. dist., with scribe marks T26 R9W S20 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W

S 17 | S 16  
S 20 | S 21  
1973

No other suitable trees available within limits.

Deposit corner stone alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, determined at record bearing and distance from the remains of the original bearing trees:

A decayed fir stump, 18 ins. diam., bears N.  $3^{\circ}$  E., 46 lks. dist., no marks visible.

A root hole, bears S.  $68\frac{3}{4}^{\circ}$  W., 38 lks. dist., with a down cedar alongside, 16 ins. diam., with illegible scribe marks visible on decayed blaze.

and bearing trees of which I have no record

A fir, 16 ins. diam., bears N.  $27\frac{1}{2}^{\circ}$  E., 33 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N.  $83^{\circ}$  W., 10 lks. dist., with scribe marks  $\frac{1}{4}$  S17 BT visible on open blaze.