

15965

Remonumentation of Certain Original Corner Points,  
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W  
S 17 | S 16  
1973

The ¼ sec. cor. of secs. 9 and 16, determined at record bearing and distance from the remains of the original bearing trees:

- A fir, 32 ins. diam., bears N. 30° W., 39 lks. dist., with illegible scribe marks visible on open blaze.
- A fir snag, 34 ins. diam., bears S. 79° W., 40 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W  
S 9  
S 16  
1973

from which a new bearing tree

- A fir, 10 ins. diam., bears S. 62° E., 20 lks. dist., mkd. ¼ S16 BT.

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance from the remains of the original bearing trees:

- A root hole, bears N. 64° E., 70 lks. dist., with a down hemlock alongside, 20 ins. diam., with scribe marks R9W S20 BT visible on open blaze.
- A fir stump, 40 ins. diam., bears S. 63° E., 32 lks. dist., with scribe marks T26S R9W S29 BT visible on open blaze.
- A fir stump, 40 ins. diam., bears S. 28° W., 68 lks. dist., with scribe marks T26S R9W S30 BT visible on open blaze.
- A fir stump, 30 ins. diam., bears N. 36° W., 38 lks. dist., with scribe marks T26S R9W S19 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 9 W  
S 19 | S 20  
S 30 | S 29  
1973