

Remonumentation of Certain Original Corner Points,  
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

No other suitable trees available within limits.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 29, determined at record bearing and distance from the original bearing trees:

A fir, 55 ins. diam., bears N.  $17^{\circ}$  W., 57 lks. dist., with illegible scribe marks visible on bark.

A cedar, 60 ins. diam., bears S.  $31\frac{1}{2}^{\circ}$  W., 40 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 9 W  
 $\frac{1}{4}$  S 20  
S 29  
1973

The witness cor. to the  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, marked with original marks W|C on a sandstone ledge, from which the remains of the original bearing trees:

A fir stump, 38 ins. diam., bears S.  $19^{\circ}$  E., 5 lks. dist., no marks visible.

A fir stump, 36 ins. diam., bears S.  $35\frac{1}{2}^{\circ}$  W., 32 lks. dist., no marks visible.

and a bearing tree of which I have no record

A fir, 16 ins. diam., bears N.  $71^{\circ}$  W., 60 lks. dist., with scribe marks WC  $\frac{1}{4}$  S19 BT visible on open blaze.

At the corner point

Seat a brass tablet,  $3\frac{1}{4}$  ins. diam.,  $3\frac{1}{2}$  ins. stem, in drill hole, in ledge, with top mkd.

↑  
W|C  
T 26 S R 9 W  
 $\frac{1}{4}$   
S 19|S 20  
1973

from which a new bearing tree

A fir, 8 ins. diam., bears S.  $19^{\circ}$  W., 58 lks. dist., mkd. X BT.