

Dependent Resurvey of a Portion of the East Boundary,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by William H. Byars,
U. S. Deputy Surveyor, in 1881,
and the remonumentation by Hans W. Thielsen,
Cadastral Surveyor, in 1958)

Beginning at the cor. of secs. 13, 18, 19, and 24, on
the E. bdy. of the Tp., monumented with an iron pipe,
1 in. diam., firmly set, projecting 6 ins. above ground,
with aluminum cap mkd.

T 32 S			
R 8 W		R 7 W	
S 13		S 18	
S 24		S 19	
1958			

from which the remaining original bearing trees

A madrone, 16 ins. diam., bears N. 30° E., 75
lks. dist., no marks visible on opened blaze.
(Record, 81 lks.)

A fir, 28 ins. diam., bears S. 55° W., 23 lks.
dist., with illegible scribe marks visible
on opened and burned blaze.

A live oak, 12 ins. diam., bears N. 58½° W., 76
lks. dist., with scribe marks R8W S13 visible
on partially opened blaze. (Record, N. 55° W.,
81 lks.)

and bearing trees mkd. by Thielsen

A fir, 33 ins. diam., bears N. 17° E., 85 lks.
dist., with healed blaze. (Record, N. 19° E.)

A fir, 18 ins. diam., bears S. 71½° E., 54 lks.
dist., with healed blaze. (Record, S. 70½° E.)

A fir, 20 ins. diam., bears S. 71° W., 74 lks.
dist., with healed blaze. (Record, S. 72½° W.,
75 lks.)

A fir, 20 ins. diam., bears N. 75½° W., 47 lks.
dist., with healed blaze. (Record, N. 74° W.)

N. 0° 17' W., bet. secs. 13 and 18, marking and blazing
the true line.

Ascend 200 ft. over SE. slope, through medium timber
and dense undergrowth, across partially logged area.

11.85 Spur, slopes E.; desc. 140 ft. over steep NE. slope.

19.36 Point for the S 1/16 sec. cor. of secs. 13 and 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, and in a mound of stone, 2½ ft. base,
to top, with brass cap mkd.

S 1/16		
S 13		S 18
1973		

from which