

Dependent Resurvey of a Portion of the East Boundary,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 5 ins. diam., bears S. 11° E., $51\frac{1}{2}$ lks.
dist., mkd. X BT.

A fir, 7 ins. diam., bears S. $52\frac{1}{2}^{\circ}$ W., 19 lks.
dist., mkd. X BT.

Ascend 5 ft. along E. slope.

76.80 Leave timber and undergrowth, enter open rocky slide
area, edge bears NW. and SE.; desc. 20 ft. over vertical
E. slope.

77.44 True point for the cor. of secs. 7, 12, 13, and 18, at
proportionate distance; there is no remaining evidence
of the original corner. The corner point falls on
vertical rock face of slide area where it is impractic-
able to establish a permanent monument.

Land, mountainous except for narrow valley bottom.
Soil, rocky clay with rock outcroppings.
Timber, fir, pine, oak, madrone, cedar, yew, chinquapin,
and alder; undergrowth, poison oak, manzanita, ceanothus,
salal, Oregon grape, and fern.

N. $0^{\circ} 17'$ W., bet. secs. 7 and 12.

Ascend 40 ft. along steep E. slope, changing to SE.
slope, across open rocky slide area.

6.30 Leave open slide area, edge bears NE. and SW.; enter
medium timber and dense undergrowth.

7.00 Spur, slopes E.; desc. 200 ft. along E. slope, changing
to steep NE. slope.

13.75 Asphalt surfaced road, 30 lks. wide, bears N. 75° W.
and S. 65° E., in curve.

16.40 Cow Creek, 120 lks. wide, course N. 75° W.; asc. 115 ft.
over rocky SW. slope.

17.70 Center of Southern Pacific Railroad tracks, tracks bear
N. 75° W. and S. 65° E., in curve.

19.36 Point for the S $1/16$ sec. cor. of secs. 7 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins.
in the ground, and in a mound of stone, 3 ft. base, to
top, with brass cap mkd.

S $1/16$
S $12 | S 7$
1973

from which

A fir, 12 ins. diam., bears S. $71\frac{1}{2}^{\circ}$ E., 118 lks.
dist., mkd. S $1/16$ S7 BT.

A fir, 11 ins. diam., bears N. $6\frac{1}{2}^{\circ}$ W., 68 lks.
dist., mkd. S $1/16$ S12 BT.

Ascend 15 ft. over SW. slope.