

15973

Dependent Resurvey of a Portion of the East Boundary,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS 20.20	Spur, slopes W.; desc. 125 ft. over steep NW. slope.
23.40	Creek, 5 lks. wide, course S. 70° W.; asc. 470 ft. over SE. slope.
37.75	Spur, slopes SW.; desc. 15 ft. over NW. slope.
38.72	The ¼ sec. cor. of secs. 7 and 12, perpetuated and recorded by Norman D. Price, Registered Land Surveyor No. 33, in 1954, subsequently perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R	T 32 S	R
8	S 12 S 7	7
W	¼	W
	1967	

from which the remains of the original bearing trees

A pine snag, 45 ins. diam., bears S. 5½° W., 102 lks. dist., no marks visible. (Record, S. 4° W.)
This tree was rescribed ¼ S R8W RS33 BT.

and a bearing tree mkd. by Powell

A ponderosa pine, 7 ins. diam., bears N. 43¾° E., 28 lks. dist., with scribe marks ¼ S7 CS BT visible on partially healed double blaze.

and a new bearing tree

A fir, 12 ins. diam., bears S. 12½° W., 38 lks. dist., mkd. ¼ S12 BT.

N. 0° 07' W., beginning new measurement.

Descend 1 ft. over NW. slope.

0.15	Ravine, drains S. 60° W.; asc. 150 ft. over SE. slope, changing to E. slope.
8.00	Head of ravine, drains S. 25° E.; asc. 235 ft. over S. slope, changing to SE. slope.
9.40	Dirt road, 20 lks. wide, bears S. 85° E. and S. 85° W.
19.74	Point for the N 1/16 sec. cor. of secs. 7 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 12 S 7
1973

from which

A ponderosa pine, 18 ins. diam., bears S. 77½° E., 6½ lks. dist., mkd. N 1/16 S7 BT.

A ponderosa pine, 15 ins. diam., bears S. 49½° W., 10½ lks. dist., mkd. N 1/16 S12 BT.

Ascend 90 ft. over SE. slope.