

Dependent Resurvey of a Portion of the East Boundary,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

23.75

Spur, slopes SW.; desc. 30 ft. along broken W. slope.

34.50

Head of ravine, drains S. 70° W.; asc. 145 ft. over SE. slope.

38.70

Spur, slopes SW.; desc. 15 ft. over NW. slope.

39.48

The cor. of secs. 1, 6, 7, and 12, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R	T 32 S	R
8	S 1 S 6	7
W	S 12 S 7	W
1967		

from which the remains of the original bearing trees

A sawed and decayed pine stump, size indeterminate, bears N. 83° E., 11 lks. dist., no marks visible. (Record, N. 80° E., 6 lks.)

A root hole, bears S. 48½° E., 141 lks. dist., dist. (Record, S. 50° E., 140 lks.)

A root hole, bears S. 8° W., 66 lks. dist., with a down fir alongside, 24 ins. diam., with scribe marks S R8 visible on bark.

and bearing trees mkd. by Powell

A fir, 16 ins. diam., bears N. 65½° E., 57 lks. dist., with pitched over partially healed blaze.

A madrone, 10 ins. diam., bears S. 41° E., 6½ lks. dist., with scribe marks T32S R7W S7 CS BT visible on partially healed double blaze.

A fir, 17 ins. diam., bears S. 40½° W., 29½ lks. dist., with pitched over partially healed double blaze.

A fir, 12 ins. diam., bears N. 53½° W., 20½ lks. dist., with pitched over partially healed double blaze.

Land, mountainous except for narrow valley bottom. Soil, rocky clay with rock outcroppings. Timber, fir, pine, oak, madrone, cedar, yew, and alder; undergrowth, manzanita, poison oak, salal, Oregon grape, and fern.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 32 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Richard S. Dickerson,
U. S. Deputy Surveyor, in 1883)