

15975

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1968, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T. 32 S R 8 W

14 | 13

23 | 24

1968

from which the remains of the original bearing trees

A madrone snag, 15 ins. diam., bears N. 70° E., 40 lks. dist., no marks visible on decayed blaze.

A fir, 67 ins. diam., bears S. 89° W., 31 lks. dist., with scribe marks T32S R8W S23 visible on bark blaze. (Record, 29 lks.)

and the remains of bearing trees mkd. by Powell

A sawed fir stump, 48 ins. diam., bears S. 71° E., 63 lks. dist., with scribe marks T32S R8W CS visible on partially healed blaze.

A tan oak, 18 ins. diam., bears S. 12° W., 22½ lks. dist., with scribe marks T32S R8W S23 BT visible on partially healed double blaze.

A madrone, 12 ins. diam., bears N. 36° W., 50½ lks. dist., with scribe marks T32S R8W S14 CS BT visible on partially healed double blaze.

and a new bearing tree

A fir, 40 ins. diam., bears N. 61° E., 97 lks. dist., mkd. T32S R8W S13 BT.

N. 0° 01' E., bet. secs. 13 and 14, marking and blazing the true line.

Descend 80 ft. over NE. slope, through scattered timber and dense undergrowth.

2.20 Creek, 1 lk. wide, course N. 70° E.; asc. 5 ft. along E. slope.

3.55 Spur, slopes E.; desc. 40 ft. over NE. slope.

5.55 Creek, 5 lks. wide, course S. 50° E.; asc. 780 ft. over SE. slope, changing to S. slope.

10.70 Asphalt surfaced road, 30 lks. wide, bears E. and W.

38.86 Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 8 W

S 14 | S 13

1975