

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	N. 89° 52' W., bet. secs. 12 and 13.
	Ascend 40 ft. over nearly vertical rock face in slide area.
0.70	Leave slide area, enter timber and undergrowth, edge bears NW. and SE.; asc. 580 ft. over broken E. slope.
27.25	Asphalt surfaced road, 30 lks. wide, bears N. 20° W. and S. 20° E.
29.25	Spur, slopes NE.; desc. 70 ft. over NW. slope.
36.60	Asphalt surfaced road, 30 lks. wide, bears N. 60° E. and S. 60° W.
38.77	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 32 S R 8 W $\frac{1}{4}$ $\frac{S 12}{S 13}$ 1975
	from which
	A fir, 7 ins. diam., bears N. 64° E., 60 lks. dist., mkd. $\frac{1}{4}$ S12 BT.
	A fir, 6 ins. diam., bears S. 10 $\frac{1}{2}$ ° W., 55 lks. dist., mkd. $\frac{1}{4}$ S13 BT.
	Corner is located in a ravine, drains NE.
	Ascend 130 ft. over SE. slope.
40.10	Asphalt surfaced road, 30 lks. wide, bears N. and S.
43.80	Spur, slopes NE.; desc. 220 ft. over NW. slope.
58.80	Creek, 1 lk. wide, course N. 60° E.; asc. 145 ft. over SE. slope.
62.60	Spur, slopes N. 50° E.; desc. 25 ft. over NW. slope.
64.70	Ravine, drains N. 30° E.; asc. 450 ft. over broken NE. slope.
77.54	The cor. of secs. 11, 12, 13, and 14.
	Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak, madrone, alder, and maple; undergrowth, poison oak, manzanita, ceanothus, hazel, salal, and Oregon grape.
	N. 0° 25' E., bet. secs. 11 and 12.
	Descend 30 ft. along broken E. slope.