

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

10.35

Ridge, bears N. 10° E. and S. 10° W.; desc. 210 ft. over NW. slope.

19.43

Point for the S 1/16 sec. cor. of secs. 11 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 11|S 12
1975

*Fd. Renewed
5/23/91 R. Brown
C.S. 63/129*

FO BC i 3 BTs
i 6' Post

By R Quimby

8/20/14 CS

65/86-4
Area Burnt 7-2013

from which

A sugar pine, 15 ins. diam., bears N. 40½° E., 110 lks. dist., mkd. S 1/16 S12 BT.

A fir, 23 ins. diam., bears N. 87½° W., 174 lks. dist., mkd. S 1/16 S11 BT.

Descend 540 ft. over NW. slope.

22.50

Gravelled road, 25 lks. wide, bears N. 20° E. and S. 20° W.

24.60

Same road, 25 lks. wide, bears N. 60° E. and S. 10° W., in curve.

25.80

Gravelled road, 25 lks. wide, bears N. 20° E. and S. 70° W., in curve.

36.30

Asphalt surfaced road, 30 lks. wide, bears N. 60° E. and S. 60° W.

38.86

Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 32 S R 8 W

¼
S 11|S 12
1975

from which

A fir, 20 ins. diam., bears S. 81° E., 107 lks. dist., mkd. ¼ S12 BT.

A fir, 27 ins. diam., bears N. 52° W., 140 lks. dist., mkd. ¼ S11 BT.

Descend 85 ft. over NW. slope.

42.80

Spur, slopes NW.; desc. 150 ft. over NE. slope.

45.80

Ravine, drains N. 70° W.; asc. 20 ft. over SW. slope.

47.90

Spur, slopes N. 70° W.; desc. 200 ft. over broken NW. slope.

58.29

Point for the N 1/16 sec. cor. of secs. 11 and 12.