

15979

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 11 S 12 1975</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 18° E., 78 lks. dist., mkd. N 1/16 S12 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 32½° W., 77½ lks. dist., mkd. N 1/16 S11 BT.</p> <p>Descend 150 ft. over NW. slope.</p>
66.40	West Fork of Cow Creek, 35 lks. wide, course N. 40° E.; asc. 150 ft. over broken SE. slope.
68.90	Asphalt surfaced road, 35 lks. wide, bears N. 30° E. and S. 30° W.
77.72	<p>The cor. of secs. 1, 2, 11, and 12, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1968, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 32 S R 8 W S 2 S 1 S 11 S 12 1968</p> <p><i>pd. ok DCSO 9/22/92 CS 6/4/32</i></p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A madrone, 13 ins. diam., bears N. 40° E., 51 lks. dist., no marks visible. (Record, 53 lks.)</p> <p style="padding-left: 40px;">A fir, 57 ins. diam., bears S. 20° W., 66 lks. dist., with scribe marks T32S visible on bark blaze. This tree was rescribed by Powell, with scribe marks T32S R8W S11 CS BT visible on bark blaze.</p> <p style="padding-left: 40px;">A fir root crown, size indeterminate, bears N. 35° W., 59 lks. dist. (Record, N. 40° W., 57 lks.)</p> <p>and bearing trees mkd. by Powell</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 21° E., 40½ lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A tan oak, 16 ins. diam., bears S. 77° E., 27 lks. dist., with scribe marks T32S R8W S12 CS BT visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A tan oak, 7 ins. diam., bears N. 85° W., 21 lks. dist., with scribe marks T32S R8W S2 CS BT visible on partially healed double blaze.</p> <p>From this point, a point established by person(s) unknown monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 15 ins. above ground, bears North, 0.015 chs. dist.</p>