

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, pine, cedar, oak, madrone, chinquapin,
alder, and maple; undergrowth, poison oak, manzanita,
hazel, ceanothus, salal, and Oregon grape.

From the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with
the original corner tree, a hollow live oak, 20 ins.
diam., no marks visible on decayed N. face.

from which the remains of the original bearing trees

A madrone root crown, size indeterminate, bears
N. 65° E., 24 lks. dist.

A hollow live oak, 17 ins. diam., bears S. 54° E.,
79 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, in center of original corner tree, with
brass cap mkd.

T 32 S R 8 W

$\frac{1}{4}$ $\frac{S 1}{S 12}$

1975

from which new bearing trees

A live oak, 9 ins. diam., bears N. 10° E., 26 lks.
dist., mkd. $\frac{1}{4}$ S1 BT.

A fir, 12 ins. diam., bears S. 56° E., 56½ lks.
dist., mkd. $\frac{1}{4}$ S12 BT.

S. 89° 36' W., bet. secs. 1 and 12.

Descend 210 ft. over rocky SW. slope, through light
timber and dense undergrowth.

4.70 Southern Pacific Railroad tracks, tracks bear N. 65° W.
and S. 65° E.

7.75 Cow Creek, 120 lks. wide, course N. 20° W.; asc. 220
ft. over NE. slope, changing to N. slope.

9.00 Asphalt surfaced road, 30 lks. wide, bears NW. and SE.

16.40 Top of ascent, slopes N.; desc. 40 ft. along broken N.
slope.

19.88 Point for the W 1/16 sec. cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

W 1/16 $\frac{S 1}{S 12}$

1975

from which

A fir, 20 ins. diam., bears N. 76° E., 73½ lks.
dist., mkd. W 1/16 S1 BT.