

15383

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	Land, mountainous Soil, rocky clay. Timber, fir, pine, cedar, oak, madrone, chinquapin, and maple; undergrowth, poison oak, hazel, huckleberry, manzanita, salal, and Oregon grape.
	N. 0° 26' E., bet. secs. 14 and 15. Ascend 50 ft. over SE. slope, through scattered timber and dense undergrowth.
2.30	Ridge, bears N. 60° E. and S. 60° W.; desc. 470 ft. over NW. slope.
9.60	Dirt road, 15 lks. wide, bears N. 15° E. and S. 45° W., in curve.
19.05	Point for the S 1/16 sec. cor. of secs. 14 and 15. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S 1/16 S 15 S 14 1975 from which A madrone, 17 ins. diam., bears N. 43° E., 20½ lks. dist., mkd. S 1/16 S14 BT. A fir, 27 ins. diam., bears N. 23° W., 35½ lks. dist., mkd. S 1/16 S15 BT. Descend 50 ft. over SW. slope.
20.10	Ravine, drains W.; asc. 10 ft. over SW. slope.
21.10	Spur, slopes W.; desc. 30 ft. over NW. slope.
21.85	Dirt road, 25 lks. wide, bears N. 30° E. and S. 30° W.
22.60	Ravine, drains S. 80° W.; asc. 100 ft. over SW. slope.
23.80	Dirt road, 25 lks. wide, bears NW. and SE.
27.80	Spur, slopes W.; desc. 370 ft. over NW. slope.
31.30	Dirt road, 25 lks. wide, bears N. 30° E. and S. 30° W.
37.60	Dirt road, 20 lks. wide, bears N. 80° W. and S. 80° E.
38.10	The ¼ sec. cor. of secs. 14 and 15, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1968, monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE ¼ S 15 S 14 1968 from which the original bearing trees A fir, 22 ins. diam., bears S. 34° E., 18 lks. dist., no marks visible. (Record, S. 30° E.) This tree was rescribed by Powell, with scribe marks ¼ S14 CS BT visible on partially healed blaze.