

15985

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS					
	<p>A fir, 25 ins. diam., bears S. 29½° W., 48½ lks. dist., mkd. ¼ S14 BT.</p> <p>Ascend 5 ft. along SE. slope.</p>				
40.80	Spur, slopes N. 70° W.; desc. 400 ft. over W. slope.				
52.00	Creek, 4 lks. wide, course N. 20° W.; asc. 360 ft. over broken NE. slope.				
62.30	Spur, slopes N. 30° E.; desc. 50 ft. over NW. slope.				
64.90	Creek, 1 lk. wide, course N. 30° E.; asc. 295 ft. over W. slope.				
74.00	Abandoned dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.				
77.70	<p>The cor. of secs. 10, 11, 14, and 15, determined from the remains of the original bearing trees:</p> <p>A sawed fir stump, 36 ins. diam., bears S. 30° E., 36 lks. dist., no marks visible.</p> <p>A fir snag, 36 ins. diam., bears S. 12° W., 54 lks. dist., no marks visible.</p> <p>A sawed and decayed fir stump, 24 ins. diam., bears N. 50° W., 37 lks. dist., no marks visible. (Record, 41 lks.)</p> <p>and bearing trees mkd. by Lorne Swearingen, Registered Engineer No. 4186, in 1960</p> <p>A fir, 30 ins. diam., bears N. 71° E., 115½ lks. dist., with healed double blaze.</p> <p>A tan oak, 8 ins. diam., bears S. 62° E., 49½ lks. dist., with healed double blaze.</p> <p>A fir, 33 ins. diam., bears S. 10° W., 90 lks. dist., with healed double blaze.</p> <p>A tan oak, 9 ins. diam., bears N. 68° W., 11½ lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 8 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p>1975</p> </div> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak, and madrone; undergrowth, poison oak, hazel, huckleberry, manzanita, salal, and Oregon grape.</p>	S 10	S 11	S 15	S 14
S 10	S 11				
S 15	S 14				