

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS													
	N. 0° 02' W., bet. secs. 10 and 11.												
	Ascend 5 ft. along E. slope, through heavy timber and dense undergrowth.												
2.90	Spur, slopes E.; desc. 1,135 ft. over broken NE. slope.												
18.40	Dirt road, 15 lks. wide, bears E. and W.												
25.70	Gravelled road, 30 lks. wide, bears N. 30° W. and S. 30° E.												
32.80	West Fork of Cow Creek, 50 lks. wide, course S. 70° E.; asc. 240 ft. over S. slope.												
34.30	Asphalt surfaced road, 30 lks. wide, bears N. 70° W. and S. 70° E.												
38.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.												
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table border="0"> <tr> <td>T 32 S R 8 W</td> <td></td> <td>Fd. Ok by D. Edwards</td> </tr> <tr> <td></td> <td><math>\frac{1}{4}</math></td> <td>8/2005 M148-31</td> </tr> <tr> <td>S 10   S 11</td> <td></td> <td></td> </tr> <tr> <td>1975</td> <td></td> <td></td> </tr> </table>	T 32 S R 8 W		Fd. Ok by D. Edwards		$\frac{1}{4}$	8/2005 M148-31	S 10   S 11			1975		
T 32 S R 8 W		Fd. Ok by D. Edwards											
	$\frac{1}{4}$	8/2005 M148-31											
S 10   S 11													
1975													
	from which												
	A fir, 17 ins. diam., bears N. 36° E., 92 lks. dist., mkd. $\frac{1}{4}$ S11 BT.												
	A live oak, 10 ins. diam., bears S. 47° W., 28 lks. dist., mkd. $\frac{1}{4}$ S10 BT.												
	Ascend 580 ft. over broken S. slope.												
64.90	Top of ascent, slopes E.; desc. 10 ft. over E. slope.												
69.60	Creek, 1 lk. wide, course S. 30° E.; asc. 155 ft. over SW. slope.												
77.98	Point for the cor. of secs. 2, 3, 10, and 11, at proportionate distance; there is no remaining evidence of the original corner.												
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.												
	<table border="0"> <tr> <td>Fd. Ok by M. SMAULEY</td> <td>T 32 S R 8 W</td> <td>Fd. Ok by D. Edwards</td> </tr> <tr> <td>JULY, 2003 M143-2</td> <td>S 3   S 2</td> <td>8/2005 M148-31</td> </tr> <tr> <td></td> <td>S 10   S 11</td> <td></td> </tr> <tr> <td></td> <td>1975</td> <td></td> </tr> </table>	Fd. Ok by M. SMAULEY	T 32 S R 8 W	Fd. Ok by D. Edwards	JULY, 2003 M143-2	S 3   S 2	8/2005 M148-31		S 10   S 11			1975	
Fd. Ok by M. SMAULEY	T 32 S R 8 W	Fd. Ok by D. Edwards											
JULY, 2003 M143-2	S 3   S 2	8/2005 M148-31											
	S 10   S 11												
	1975												
	from which												
	A fir, 12 ins. diam., bears N. 9 $\frac{1}{2}$ ° E., 25 lks. dist., mkd. T32S R8W S2 BT.												
	A fir, 7 ins. diam., bears S. 83° E., 42 $\frac{1}{2}$ lks. dist., mkd. T32S R8W S11 BT.												
	A fir, 6 ins. diam., bears S. 85 $\frac{1}{2}$ ° W., 28 lks. dist., mkd. T32S R8W S10 BT.												