

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 38 ins. diam., bears S. 30° E., 140 lks. dist., mkd. $\frac{1}{4}$ S11 BT.</p> <p>Ascend 150 ft. over broken SE. slope.</p>
44.80	Gravelled road, 20 lks. wide, bears NE. and SW.
47.90	Same road, 20 lks. wide, bears SE. and NW.
50.20	Same road, 20 lks. wide, bears NE. and SW.
51.60	Top of ascent, slopes SE.; desc. 30 ft. along broken S. slope.
52.70	Gravelled road, 20 lks. wide, bears SE. and NW.
55.50	Ravine, drains SE.; asc. 65 ft. over SE. slope.
57.90	Gravelled road, 20 lks. wide, bears N. 75° E. and N. 65° W., in curve.
58.70	Spur, slopes S.; desc. 260 ft. over SW. slope.
68.20	Ravine, drains S.; asc. 110 ft. over broken SE. slope.
72.30	Top of ascent, slopes S.; desc. 25 ft. over SW. slope.
78.40	The cor. of secs. 2, 3, 10, and 11.
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak, and madrone; undergrowth, poison oak, hazel, ceanothus, salal, and Oregon grape.</p>
	<p>N. 1° 20' E., bet. secs. 2 and 3.</p> <p>Ascend 355 ft. over S. slope, through heavy timber and dense undergrowth.</p>
15.20	Dirt road, 20 lks. wide, bears S. 80° E. and N. 80° W.
15.70	Ridge, bears N. 80° W. and S. 80° E.; desc. 480 ft. over NW. slope.
31.20	Ravine, drains NE.; desc. 260 ft. over NE. slope.
39.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 S R 8 W $\frac{1}{4}$ S 3 S 2 1975</p>
	<p>from which</p> <p>A fir, 13 ins. diam., bears East, 56 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p>A fir, 25 ins. diam., bears N. 52$\frac{1}{2}$° W., 47$\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S3 BT.</p>