

15989

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	Descend 20 ft. over NE. slope.
39.90	Bottom of descent, slopes E.; asc. 15 ft. over SE. slope.
42.30	Spur, slopes N. 70° E.; desc. 275 ft. over N. slope.
47.30	Creek, 1 lk. wide, course N. 70° E.; asc. 95 ft. over SE. slope.
51.50	Spur, slopes E.; desc. 175 ft. over NE. slope.
58.50	Point for the N 1/16 sec. cor. of secs. 2 and 3. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. N 1/16 S 3 S 2 1975 from which A fir, 33 ins. diam., bears N. 49° E., 27 lks. dist., mkd. N 1/16 S2 BT. A fir, 13 ins. diam., bears N. 66° W., 29½ lks. dist., mkd. N 1/16 S3 BT. Descend 100 ft. over NE. slope.
60.60	Creek, 2 lks. wide, course E.; asc. 120 ft. over SE. slope.
65.50	Spur, slopes E.; desc. 40 ft. over NE. slope.
67.90	Bottom of descent, slopes E.; asc. 115 ft. over SE. slope.
75.80	Spur, slopes E.; desc. 70 ft. over NE. slope.
78.39	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE S 34 S 35 S 3 S 2 8 T 32 S 1967 from which the original bearing trees A fir, 30 ins. diam., bears N. 82° E., 50 lks. dist., with healed blaze. (Record, 57 lks.) A fir, 18 ins. diam., bears S. 61½° E., 41 lks. dist., with healed double blaze. (Record, S. 65° E.) A fir, 37 ins. diam., bears S. 28° W., 30 lks. dist., with scribe marks T31 R8W S3 BT visible on bark blaze. This tree was rescribed by Powell, with scribe marks T32S R8W S3 CS BT visible on partially healed blaze.