

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 30 ins. diam., bears N. 35° W., 42 lks. dist., with scribe marks T31 R8 BT visible on bark blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, chinquapin, and madrone; undergrowth, poison oak, hazel, huckleberry, manzanita, salal, and Oregon grape.

From the cor. of secs. 2, 3, 10, and 11.

N. 89° 20' W., bet. secs. 3 and 10.

Descend 10 ft. along broken S. slope, through heavy timber and dense undergrowth.

- 4.40 Wet ravine, drains SE.; asc. 90 ft. over SE. slope.
- 8.40 Spur, slopes S. 15° E.; desc. 300 ft. over SW. slope.
- 16.80 Ravine, drains S. 10° E.; asc. 260 ft. over SE. slope.
- 29.40 Top of ascent, slopes S.; desc. 30 ft. over SW. slope.
- 31.30 Head of ravine, drains S.; asc. 30 ft. over SE. slope.
- 36.60 Spur, slopes SW.; desc. 55 ft. over W. slope.
- 39.14 The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1970, monumented with an iron pipe, 1 in. diam., with brass cap, firmly set in a root hole, projecting 6 ins. above ground, alongside of which is lying the original corner tree, a fir, 26 ins. diam., with scribe marks $\frac{1}{4}$ S visible on opened blaze. The brass cap is mkd.

COUNTY SURVEYORS OFFICE

T 32 S R 8 W

$\frac{1}{4}$ $\frac{S 3}{S 10}$

1970

from which the remains of the original bearing trees

A fir snag, 17 ins. diam., bears N. 30° E., 10 lks. dist., with scribe marks BT visible on bark blaze.

A sawed fir stump, 36 ins. diam., bears S. 40° E., 21 lks. dist., with illegible scribe marks visible on bark blaze.

and the remains of bearing trees mkd. by Powell

A fir snag, 35 ins. diam., bears N. 75° E., 19 lks. dist., with scribe marks $\frac{1}{4}$ S3 CS BT visible on opened blaze.

A fir, 5 ins. diam., bears S. 67 $\frac{1}{2}$ ° W., 23 $\frac{1}{2}$ lks. dist., with healed blaze.

and a new bearing tree