

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS 11.80	Ridge, bears N. 70° E. and S. 70° W.; desc. 215 ft. over NW. slope.
20.26	Creek, 3 lks. wide, course SW.; asc. 390 ft. over broken SE. slope.
38.58	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T 32 S R 8 W $\frac{1}{4}$ S 4 S 3 1975 from which A fir, 18 ins. diam., bears S. 3° E., 55 lks. dist., mkd. $\frac{1}{4}$ S3 BT. A fir, 18 ins. diam., bears S. 82° W., 68 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S4 BT. Ascend 445 ft. over broken SE. slope.
58.50	Ridge, bears N. 40° E. and S. 40° W.; desc. 140 ft. over NW. slope.
67.60	Ravine, drains W.; asc. 110 ft. over SW. slope.
72.60	Spur, slopes W.; desc. 190 ft. over N. slope.
78.06	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T 31 S S 33 S 34 R S 4 S 3 8 T 32 S W 1967 from which the remains of the original bearing trees A sugar pine snag, 39 ins. diam., bears N. 68° E., 50 $\frac{1}{2}$ lks. dist., with scribe marks 3 S31 visible on partially opened blaze. (Record, N. 78° E., 55 lks.) A sugar pine, 38 ins. diam., bears S. 75° E., 98 lks. dist., with healed blaze. (Record, 107 lks.) A fir, 56 ins. diam., bears S. 23° W., 36 lks. dist., with scribe marks 32S R8W S visible on bark blaze. This tree was rescribed by Powell, with illegible scribe marks visible on pitched over blaze. A fir, 46 ins. diam., bears N. 75° W., 42 lks. dist., with healed blaze. (Record, N. 70° W.)