

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 33 ins. diam., bears S. 10° E., 6 lks. dist., with scribe marks $\frac{1}{4}$ S visible on burned bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 32 S R 8 W

$\frac{1}{4}$
S 5 | S 4
1975

from which a new bearing tree

A fir, 13 ins. diam., bears N. 86° W., 67 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

N. 9° 16' E., beginning new measurement.

Descend 110 ft. over NE. slope.

- 6.50 West Fork of Cow Creek, 50 lks. wide, course S. 30° E.; asc. 10 ft. along SW. slope.
- 8.00 Slotted Pen Creek, 10 lks. wide, course W.; asc. 345 ft. over S. slope.
- 9.25 Oiled road, 35 lks. wide, bears N. 75° W. and S. 75° E.
- 17.60 Spur, slopes S. 55° E.; asc. 210 ft. along E. slope.
- 32.70 Spur, slopes E.; desc. 5 ft. along E. slope.
- 35.40 Ravine, drains E.; asc. 150 ft. over SE. slope.
- 39.85 The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, monumented with an iron pipe, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S
S 32 | S 33 R
S 5 | S 4 8
T 32 S W
1967

from which the remains of the original bearing trees

A madrone, 15 ins. diam., bears N. 35° E., 35 lks. dist., no marks visible on decayed double blaze.

A sawed sugar pine stump, 30 ins. diam., bears S. 50° E., 114 lks. dist., with healed blaze.

A madrone, 10 ins. diam., bears S. 40° W., 34 lks. dist., with illegible scribe marks visible on opened double blaze.

and bearing trees mkd. by Powell