

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 12 ins. diam., bears S. 53° E., 42½ lks. dist., mkd. ¼ S8 BT.</p> <p>Ascend 460 ft. over NE. slope, changing to E. slope.</p>
42.40	Gravelled road, 15 lks. wide, bears N. 30° W. and S. 30° E.
55.10	Gravelled road, 25 lks. wide, bears N. 30° E. and S. 15° W., in curve.
57.705	<p>Point for the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \frac{\text{S } 5}{\text{S } 8} \\ 1975 \end{array}$ </p> <p>from which</p> <p>A sugar pine, 62 ins. diam., bears N. 61° W., 74 lks. dist., mkd. W 1/16 S5 BT.</p> <p>A madrone, 6 ins. diam., bears S. 13° W., 48 lks. dist., mkd. W 1/16 S8 BT.</p> <p>Ascend 60 ft. over E. slope.</p>
59.60	Ridge, bears N. 50° E. and S. 50° W.; asc. 35 ft. over NE. slope.
61.60	Top of ascent, slopes N.; desc. 50 ft. over NW. slope.
67.40	Wet ravine, drains N. 50° E.; asc. 100 ft. over E. slope.
71.60	Spur, slopes N. 25° E.; desc. 95 ft. over NW. slope.
76.94	<p>The cor. of secs. 5, 6, 7, and 8, monumented with the original basalt stone, 16 x 12 x 8 ins., firmly set, projecting 10 ins. above ground, with 2 grooves on E. face, from which the remains of the original bearing trees:</p> <p>A madrone root crown, size indeterminate, bears N. 85° E., 32 lks. dist.</p> <p>A fir, 35 ins. diam., bears S. 40° W., 31 lks. dist., with illegible scribe marks visible on burned bark blaze.</p> <p>A fir stump, size indeterminate, bears N. 25° W., 14 lks. dist., no marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{T } 32 \text{ S } \text{R } 8 \text{ W} \\ \text{S } 6 \mid \text{S } 5 \\ \text{S } 7 \mid \text{S } 8 \\ 1975 \end{array}$ </p> <p>from which new bearing trees</p>