

15997

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 7 ins. diam., bears N. 58° E., 81 lks. dist., mkd. T32S R8W S5 BT.</p> <p>A madrone, 6 ins. diam., bears S. 49° E., 21 lks. dist., mkd. T32S R8W S8 BT.</p> <p>A fir, 6 ins. diam., bears N. 15½° W., 29 lks. dist., mkd. T32S R8W S6 BT.</p> <p>Deposit corner stone alongside iron post.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak, madrone, and chinquapin; undergrowth, poison oak, manzanita, vine maple, huckleberry, salal, and Oregon grape.</p>
	<p>S. 85° 26' W., bet. secs. 6 and 7.</p> <p>Descend 175 ft. along N. slope, along S. edge of logged area, through light timber and dense undergrowth.</p>
7.00	Spur, slopes N.; desc. 75 ft. over NW. slope.
9.30	Ravine, drains N.; asc. 90 ft. over broken NE. slope.
15.40	Spur, slopes N.; desc. 165 ft. over NW. slope.
21.60	Ravine, drains N. 20° E.; asc. 100 ft. over NE. slope.
23.90	Spur, slopes N. 10° E.; desc. 45 ft. over NW. slope.
26.20	Dry creek bed, 3 lks. wide, course N. 20° E.; asc. 350 ft. over NE. slope.
35.96	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T 32 S R 8 W</p> <p>¼ <math>\frac{S 6}{S 7}</math></p> <p>1975</p>
	from which
	A fir, 6 ins. diam., bears N. 28° W., 52½ lks. dist., mkd. ¼ S6 BT.
	A fir, 54 ins. diam., bears S. 20° E., 40½ lks. dist., mkd. ¼ S7 BT.
	Ascend 210 ft. over NE. slope.
42.40	Ridge, bears N. 30° W. and S. 30° E.; desc. 675 ft. over SW. slope.
61.40	Creek, 3 lks. wide, course N. 80° W.; desc. 165 ft. over NW. slope.
70.66	The cor. of secs. 6 and 7 only, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.