

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 32 S

S 6

S 7

R 8 W

1917

from which the remains of the original bearing trees

A cedar snag, 8 ins. diam., bears N. 6° E., 58 lks. dist., with scribe marks T32S visible on opened blaze. (Record, N. 5° E.)

A fir, 13 ins. diam., bears S. 71° E., 42½ lks. dist., with healed blaze. (Record, S. 69° E., 47 lks.)

A fir, 50 ins. diam., bears S. 38° W., 11 lks. dist., no marks visible. (Record, 8 lks.)

and a bearing tree mkd. by John M. Powell, Deputy County Surveyor, in 1967

A tan oak, 7 ins. diam., bears N. 66° E., 3 lks. dist., with scribe marks T32S R8W S6 CS BT visible on partially healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, and madrone; undergrowth, poison oak, huckleberry, hazel, manzanita, and Oregon grape.

From the cor. of secs. 5, 6, 7, and 8.

N. 1° 10' W., bet. secs. 5 and 6.

Descend 820 ft. over NW. slope, along E. edge of logged area, through light timber and dense undergrowth.

10.00 Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.

19.70 Soldier Creek, 6 lks. wide, course N. 50° E.; asc. 280 ft. along E. slope.

26.80 Spur, slopes E.; desc. 180 ft. along E. slope.

37.99 The ¼ sec. cor. of secs. 5 and 6, perpetuated and recorded by Lorne Swearingen, Registered Engineer No. 4186, in 1960, monumented with a steel rod, 7/8 in. diam., firmly set, projecting 10 ins. above ground, from which the remaining original bearing tree:

A tan oak, 15 ins. diam., bears East, 29 lks. dist., with fragmentary scribe marks visible on opened burned blaze. (Record, live oak)

and bearing trees mkd. by Swearingen

A fir, 12 ins. diam., bears N. 32° E., 28 lks. dist., with healed double blaze.

A fir, 22 ins. diam., bears S. 54¾° W., 56½ lks. dist., with healed double blaze.

At the corner point