

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree mkd. by Byron

An oak, 28 ins. diam., bears N. 5° E., 190½ lks. dist., with fragmentary scribe marks visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 24 S R 7 W

S 17 | S 16

S 20 | S 21

1976

from which a reference monument

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 9½° W., 48½ lks. dist., with brass cap mkd. T24S R7W S17 RM 1976 and an arrow pointing to the corner.

No suitable trees available within limits.

Deposit axle and drive an iron bar, 72 ins. long, ½ ins. diam., 70 ins. in the ground, alongside iron post.

N. 0° 01' E., bet. secs. 16 and 17, marking and blazing the true line.

Ascend 445 ft. over S. slope, through heavy timber and dense undergrowth.

- 0.75 Paved road, 40 lks. wide, bears N. 85° W. and S. 75° E.
- 16.70 Spur, slopes S. 55° E.; desc. 60 ft. over NE. slope.
- 20.30 Ravine, drains S. 70° E.; asc. 30 ft. over SE. slope.
- 22.75 Spur, slopes S. 70° E.; desc. 40 ft. over NE. slope.
- 24.65 Creek, 1 lk. wide, course S. 80° E.; asc. 240 ft. over SE. slope.
- 32.50 Spur, slopes S. 75° E.; desc. 75 ft. over NE. slope.
- 36.25 Ravine, drains S. 70° E.; asc. 65 ft. over SE. slope.
- 37.95 Spur, slopes E.; desc. 40 ft. over NE. slope.
- 39.60 Ravine, drains E.; asc. 10 ft. over SE. slope.
- 40.34 Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼
S 17 | S 16

T 24 S R 7 W

1976