

16003

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which

- A fir, 12 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ E., $32\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S16 BT.
- A fir, 6 ins. diam., bears S. $22\frac{1}{2}^{\circ}$ W., $20\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S17 BT.

Ascend 5 ft. over SE. slope.

41.10 Ravine, drains S. 40° E.; asc. 45 ft. over SE. slope.

42.25 Spur, slopes S. 60° E.; desc. 5 ft. over NE. slope.

43.80 Ravine, drains S. 55° E.; asc. 70 ft. over SE. slope.

45.65 Spur, slopes S. 60° E.; desc. 5 ft. over NE. slope.

46.80 Ravine, drains S. 70° E.; asc. 120 ft. over SE. slope.

51.35 Ridge, bears N. 35° E. and S. 35° W.; asc. 50 ft. over SW. slope.

67.30 Top of ascent, slopes W.; desc. 35 ft. over NW. slope.

71.50 Bottom of descent, slopes W.; asc. 20 ft. over SW. slope.

80.68 The cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, from original evidence no longer in existence, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 24 S
S 8 | S 9
S 17 | S 16
R 7 W
1957

from which bearing trees mkd. by Byron

- A white oak, 13 ins. diam., bears N. $52\frac{1}{2}^{\circ}$ E., 37 lks. dist., with healed blaze.
- A fir, 21 ins. diam., bears S. 80° E., $12\frac{1}{2}$ lks. dist., with healed blaze.
- A fir, 17 ins. diam., bears S. $17\frac{1}{2}^{\circ}$ W., 35 lks. dist., with healed blaze.
- A fir, 14 ins. diam., bears N. $25\frac{1}{2}^{\circ}$ W., 55 lks. dist., with healed blaze.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, maple, oak, myrtle, alder, madrone, and chinquapin; undergrowth, salal, rhododendron, hazel, poison oak, vine maple, Oregon grape, and fern.

From the cor. of secs. 16, 17, 20, and 21.
N. $88^{\circ} 46'$ W., bet. secs. 17 and 20.
Ascend 10 ft. over SE. slope, through heavy timber and dense undergrowth.