


Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS
10.14

Point for the meander cor. of secs. 17 and 20, on left bank of Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



from which

A fir, 25 ins. diam., bears N. 41° W., 75 lks. dist., mkd. T24S R7W S17 MC BT.

and a bearing tree of which I have no record

A fir, 22 ins. diam., bears N. 68½° E., 55½ lks. dist., with scribe marks X BT visible on open blaze.

No suitable tree available within limits in sec. 20.


Descend 25 ft. over SW. slope.

11.15 Waters edge, left bank of Umpqua River, bears N. 80° W. and S. 80° E., course S. 80° E., thence across water.

33.85 Waters edge, left bank of Umpqua River, bears N. 80° E. and S. 80° W.; asc. 5 ft. over SE. slope.

34.47 Point for the meander cor. of secs. 17 and 20, on left bank of Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.



from which

A sandstone boulder, 8 x 5 x 3 ft. above ground, bears N. 60½° W., 16 lks. dist., mkd. X BO.

A sandstone boulder, 6 x 3 x 3 ft. above ground, bears S. 62° W., 37 lks. dist., mkd. X BO.

Ascend 110 ft. over precipitous SE. slope.

37.75 Dirt road, 30 lks. wide, bears N. 75° E. and S. 75° W.

40.40 The ¼ sec. cor. of secs. 17 and 20, perpetuated and recorded by James W. Byron, Deputy Surveyor, in 1958, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.