

18005

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

## COUNTY SURVEYORS OFFICE

S 17

¼ S 20

1958

from which the remains of the original bearing trees

A sawed fir stump, 35 ins. diam., bears S. 86° W.,  
31½ lks. dist., with scribe marks BT visible on  
open blaze. (Record, S. 88° W., 30 lks.)

and the remains of bearing trees mkd. by Byron

A white oak, 10 ins. diam., bears N. ½° W., 17  
lks. dist., with healed blaze.

A fir snag, 15 ins. diam., bears S. 31° W., 32  
lks. dist., with scribe marks ¼ S20 CS BT  
visible on open blaze.

and a new bearing tree

A white oak, 10 ins. diam., bears S. 3½° E., 58  
lks. dist., mkd. ¼ S20 BT.

S. 89° 47' W., beginning new measurement.

Ascend 260 ft. over precipitous SE. slope.

- 17.45 Ravine, drains S. 35° E.; asc. 90 ft. over SE. slope.
- 22.00 Spur, slopes S. 10° E.; desc. 10 ft. over SW. slope.
- 25.25 Ravine, drains S. 5° E.; asc. 145 ft. over SE. slope.
- 36.70 Ridge, bears N. 35° E. and S. 35° W.; desc. 60 ft. over  
NW. slope.
- 40.45 The cor. of secs. 17, 18, 19, and 20, perpetuated and  
recorded by James W. Byron, Deputy County Surveyor, in  
1960, monumented with an iron post, 1½ ins. diam., firmly  
set, projecting 12 ins. above ground, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

T 24 S R 7 W

S 18 | S 17

S 19 | S 20

1960

from which the remains of the original bearing trees

A fir snag, 44 ins. diam., bears N. 1° E., 39½ lks.  
dist., with scribe marks T24S R7W S17 visible  
on open blaze. (Record, 36 lks.)

A root hole, bears S. 75° E., 46 lks. dist., with  
a down fir alongside, 18 ins. diam., no marks  
visible.

and the remains of bearing trees mkd. by Byron

A fir, 15 ins. diam., bears N. 44° E., 105 lks.  
dist., with scribe marks 4S R7W S17 CS visible  
on bark blaze.

A grand fir stump, 15 ins. diam., bears S. 78½° E.,  
34½ lks. dist., with healed blaze.