

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

| CHAINS |  |
|--------|--|
|        | <p>A grand fir, 13 ins. diam., bears S. 60½° W., 98½ lks. dist., with healed blaze.</p> <p>A grand fir, 14 ins. diam., bears N. 5° W., 100 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 5 ins. diam., bears S. 13¾° E., 43½ lks. dist., mkd. T24S R7W S20 BT.</p> <p>Land, mountainous.<br/>Soil, rocky clay.<br/>Timber, fir, hemlock, maple, oak, myrtle, madrone, alder, and chinquapin; undergrowth, salal, rhododendron, hazel, vine maple, poison oak, Oregon grape, and fern.</p>   |
|        | <p>N. 0° 04' W., bet. secs. 17 and 18.</p> <p>Descend 100 ft. over N. slope, through scattered timber and dense undergrowth.</p>   |
| 5.30   | Creek, 3 lks. wide, course E.; asc. 350 ft. over SW. slope.  |
| 15.15  | Dirt road, 30 lks. wide, bears N. 75° W. and S. 60° E.   |
| 15.85  | Ridge, bears N. 30° W. and S. 30° E.; desc. 220 ft. over NE. slope.  |
| 29.35  | Creek, 3 lks. wide, course N. 60° E.; asc. 95 ft. over SE. slope.  |
| 32.10  | Ridge, bears N. 65° W. and S. 65° E.; desc. 75 ft. over NE. slope.   |
| 36.55  | Creek, 5 lks. wide, course S. 20° E.; asc. 40 ft. over SW. slope.  |
| 38.15  | Spur, slopes S. 40° W.; asc. 30 ft. over SW. slope.  |
| 40.03  | <p>The ¼ sec. cor. of secs. 17 and 18, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1½ ins. diam., loosely set, projecting 18 ins. above ground, damaged by logging operation, with brass cap mkd. COUNTY SURVEYORS OFFICE T24S ¼ S18 S17 R7W 1961, from which the remains of the original bearing trees</p> <p>A sawed cedar stump, 38 ins. diam., bears N. 9° W., 11 lks. dist., with scribe marks 4 S visible on open blaze, rescribed by Byron, in 1961, with ¼ S18 C visible on open blaze alongside.</p> <p>and the remains of a bearing tree mkd. by Byron</p> <p>A root hole, bears S. 66° E., 36 lks. dist., with a down fir alongside, 12 ins. diam., with scribe marks ¼ S17 CS BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |