

16007

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

S 18 | S 17
T 24 S R 7 W
1975

from which new bearing trees

A fir, 19 ins. diam., bears N. $38\frac{1}{2}^{\circ}$ E., 109 lks.
dist., mkd. $\frac{1}{2}$ S17 BT.

A fir, 4 ins. diam., bears N. $79\frac{1}{2}^{\circ}$ W., 57 lks.
dist., mkd. $\frac{1}{2}$ S18 BT.

Deposit iron post alongside iron post.

N. $0^{\circ} 03'$ E., beginning new measurement.

Ascend 185 ft. over SW. slope.

- 6.80 Gravelled road, 30 lks. wide, bears N. 70° W. and
S. 70° E.
- 8.50 Ridge, bears N. 85° W. and S. 70° E.; desc. 105 ft. over
NE. slope.
- 13.40 Gravelled road, 30 lks. wide, bears N. 55° W. and
S. 55° E.
- 19.15 Ravine, drains N. 80° E.; asc. 10 ft. over SE. slope.
- 20.095 Point for the N 1/16 sec. cor. of sec. 17 only. This
point falls in gravelled road, 40 lks. wide, bears
N. 50° E. and S. 50° W.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 42 ins.
in the ground, the top 14 ins. below the road surface,
with brass cap mkd.
- N 1/16
S 17
1976
- from which
- A cedar, 18 ins. diam., bears N. $8\frac{1}{2}^{\circ}$ E., $135\frac{1}{2}$ lks.
dist., mkd. N 1/16 S17 BT.
- A fir, 4 ins. diam., bears S. 15° E., $25\frac{1}{2}$ lks.
dist., mkd. N 1/16 S17 BT.
- An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24
ins. in the ground, for a reference monument,
bears N. $72\frac{1}{2}^{\circ}$ E., 29 lks. dist., with brass cap
mkd. N 1/16 S17 RM 1976 and an arrow pointing
to the corner.
- Ascend 30 ft. over SE. slope.
- 21.65 Ridge, bears N. 60° E. and S. 60° W.; desc. 50 ft. over
NE. slope.
- 24.25 Ravine, drains N. 55° E.; asc. 5 ft. over SE. slope.
- 24.35 Spur, slopes N. 70° E.; desc. 25 ft. over NE. slope.
- 25.55 Ravine, drains N. 85° E.; asc. 30 ft. over SE. slope.