

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
27.20	Spur, slopes E.; desc. 25 ft. over NE. slope.
28.55	Ravine, drains E.; asc. 40 ft. over SE. slope.
31.45	Spur, slopes S. 80° E.; desc. 20 ft. over NE. slope.
34.65	Ravine, drains E.; asc. 2 ft. over SE. slope.
35.00	Spur, slopes N. 80° E.; desc. 5 ft. over NE. slope.
35.50	Creek, 1 lk. wide, course N. 70° E.; asc. 10 ft. over SE. slope.
36.50	Creek, 1 lk. wide, course S. 60° E.; asc. 50 ft. over SE. slope.
40.19	The cor. of secs. 7, 8, 17, and 18, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, from original evidence no longer in existence, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S
S 7 | S 8
S 18 | S 17
R 7 W
1957

from which the remains of bearing trees mkd. by Byron

A fir snag, 16 ins. diam., bears N. 41¼° E., 88½ lks. dist., with scribe marks 24S R7W S8 CS BT visible on open blaze.

A grand fir, 20 ins. diam., bears S. 50° E., 73 lks. dist., with healed blaze.

A root crown, bears S. 60¼° W., 180 lks. dist., with a down fir alongside, 8 ins. diam., with scribe marks T24S R7W S18 CS BT visible on open blaze.

A fir snag, 48 ins. diam., bears N. 63° W., 41 lks. dist., with scribe marks T24S R7W S7 CS visible on bark blaze.

and new bearing trees

A fir, 5 ins. diam., bears N. 45½° E., 11½ lks. dist., mkd. T24S R7W S8 BT.

A grand fir, 8 ins. diam., bears S. 59¼° W., 201 lks. dist., mkd. T24S R7W S18 BT.

A fir, 6 ins. diam., bears N. 84¾° W., 27 lks. dist., mkd. T24S R7W S7 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, maple, oak, madrone, myrtle, alder, cedar, and chinquapin; undergrowth, salal, rhododendron, hazel, vine maple, poison oak, Oregon grape, and fern.

From the cor. of secs. 8, 9, 16, and 17.

N. 89° 50' W., bet. secs. 8 and 17.