

16009

390

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	Descend 160 ft. over SW. slope, through heavy timber and dense undergrowth.
5.95	Ravine, drains S. 65° W.; desc. 35 ft. over SW. slope.
7.85	Ravine, drains S. 25° W.; asc. 10 ft. over SE. slope.
9.45	Spur, slopes S. 45° W.; desc. 250 ft. over SW. slope.
19.05	Ravine, drains N. 40° W.; asc. 2 ft. over NE. slope.
19.15	Spur, slopes N. 65° W.; desc. 10 ft. over SW. slope.
20.45	Ravine, drains N. 60° W.; desc. 90 ft. over NW. slope.
23.95	Ravine, drains N. 50° W.; asc. 145 ft. over SE. slope.
30.85	Top of ascent, slopes S.; desc. 15 ft. over SW. slope.
34.00	Ravine, drains S. 5° E.; asc. 30 ft. over SE. slope.
39.95	The ½ sec. cor. of secs. 8 and 17, perpetuated and recorded by Milo Godfrey, Deputy County Surveyor, in 1963, monument with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 24 S ½ $\frac{S 8}{S 17}$ R 7 W 1963
	from which the remains of the original bearing trees
	A root crown, bears N. 10° W., 32 lks. dist., with a down oak alongside, 43 ins. diam., no marks visible on open decayed blaze.
	and bearing trees mkd. by Godfrey
	A fir, 12 ins. diam., bears N. 44½° W., 55 lks. dist., with healed blaze.
	A fir, 12 ins. diam., bears S. 43° E., 26½ lks. dist., with healed blaze.
	Corner is located at top of ascent, slopes S.

	N. 89° 45' W., beginning new measurement.
	Descend 15 ft. over SW. slope.
1.80	Ravine, drains S. 5° E.; asc. 400 ft. over SE. slope.
13.85	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
16.15	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
19.86	Point for the W 1/16 sec. cor. of secs. 8 and 17.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W 1/16 $\frac{S 8}{S 17}$ 1975