

16011

Subdivision of Section 17, T. 24 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS
37.50

Junction of gravelled roads, 40 lks. wide, bears
N. 60° W., S. 60° E., and N. 25° E.

39.65

Point for the center $\frac{1}{4}$ sec. cor. of sec. 17, at inter-
section with the E. and W. center line.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

C $\frac{1}{4}$ S 17
T. 24 S R 7 W
1976

from which

A grand fir, 6 ins. diam., bears S. 24° W., 32 $\frac{1}{2}$
lks. dist., mkd. C $\frac{1}{4}$ S17 BT.

A fir, 8 ins. diam., bears N. 58 $\frac{1}{2}$ ° W., 24 $\frac{1}{2}$ lks.
dist., mkd. C $\frac{1}{4}$ S17 BT.

Ascend 235 ft. over SE. slope.

41.35

Enter timber, edge bears N. 50° E. and S. 50° W.

48.25

Spur, slopes S. 85° E.; desc. 95 ft. over NE. slope.

53.00

Dirt road, 20 lks. wide, bears N. 45° W. and S. 45° E.,
also enter open field, edge bears same as road.

54.00

Ditch, 1 lk. wide, drains S. 20° E.; asc. 20 ft. over
gentle SE. slope.

54.30

Gravelled road, 15 lks. wide, bears N. 25° W. and
S. 25° E.

59.755

Point for the center N $\frac{1}{16}$ sec. cor. of sec. 17.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

C
N $\frac{1}{16}$ | S 17
C
1976

from which

An apple tree, 8 ins. diam., bears S. 52 $\frac{1}{4}$ ° E.,
7 lks. dist., mkd. CN $\frac{1}{16}$ S17 BT.

An oak, 28 ins. diam., bears S. 41 $\frac{1}{2}$ ° W., 224 lks.
dist., mkd. CN $\frac{1}{16}$ S17 BT.

Ascend 10 ft. over gentle SE. slope.

63.00

Top of ascent, slopes E.; desc. 30 ft. over NE. slope.

63.40

Enter timber, edge bears N. 65° W. and S. 65° E.

65.65

Creek, 2 lks. wide, course N. 85° E.; asc. 20 ft. over
SE. slope.

70.45

Spur, slopes E.; desc. 10 ft. over NE. slope.

71.50

Creek, 2 lks. wide, course S. 70° E.; asc. 10 ft. over
SE. slope.